

CM-5403-PAR

54pcs LED Par Light



FEATURES

- Wide Voltage Compatibility: AC 90V–220V, 50/60Hz – adaptable to global power supply.
- High-Brightness RGBW Light Source: 54×3W LEDs (R12/G18/B18/W6) for rich color mixing.
- Adjustable Color Temperature: Linear 3200K–7200K tuning for various scene needs.
- Professional Strobe & Dimming: 1–25Hz electronic strobe + 0–100% flicker-free linear dimming.
- Selectable Beam Angle: 15°/25°/45° optional for different lighting effects.

EFFECT PHOTO



CM-5403-PAR

54pcs LED Par Light

SPECIFICATIONS

Input voltage	: C90V-220V
Frequency	: 50Hz -60 Hz
Rated power	: 200W
Light source	: 54x3W lamp beads (R12, G18, B18, W6)
Light source life	: 6-10 million hours
Color Temperature	: Adjustable 3000K-6000K
Color	: RGBW induction color mixing into a variety of colors, built-in macro function (0-100% saturation adjustable)
LED Angle	: 15°C, 25°C, 45°C (optional)
Control	: DMX512, master-slave control, self-propelled
Channel	: 8CH channel
Display	: call a variety of scenes, the built-in program can be directly called to execute
Color temperature correction	: 3200K ~ 7200K linear adjustment
Strobe	: independent electronic strobe 1-25Hz, can be random strobe, pulse strobe, synchronous asynchronous strobe, monochrome, mixed color temperature strobe
Features	: cast aluminum shell, high light efficiency, uniform light mixing, stable performance. With one in and one out of the hand 1 meter long power supply, signal line. 1024-level ultra-high grayscale dimming softer 0-100% independent electronic linear dimming, camera video real flicker-free Master-slave self-propelled automatic synchronization function, console normal control self-propelled permanent synchronization
Lamps and lanterns connection	: three-core signal line IN/OUT; power line in/out
Ambient temperature	: -20°C ~ 40°C
Sound control sensitivity	: 65-130dB
Working environment humidity	: <90%
Product size	: 28 cm*24 cm*30 cm
Net weight	: 4 KG